

AD-A128 031

PICOSECOND X-RAY GENERATION FROM PICOSECOND
PHOTOELECTRON PULSES(U) CALIFORNIA UNIV SAN DIEGO LA
JOLLA DEPT OF CHEMISTRY S WILLIAMSON ET AL. APR 83

1/1


UNCLASSIFIED

TR-14 N00014-78-C-0325

F/G 28/6

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

12

ADA 128031

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 14	2. GOVT ACCESSION NO. AD A128031	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) PICOSECOND X-RAY GENERATION FROM PICOSECOND PHOTOELECTRON PULSES		5. TYPE OF REPORT & PERIOD COVERED Technical
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Steve Williamson and Gerard Mourou Charles G. Dupuy, Philippe Bado and Kent R. Wilson		8. CONTRACT OR GRANT NUMBER(s) ONR-N00014-78 C-0325
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of Chemistry, B-014 University of California at San Diego La Jolla, CA 92093		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Arlington, VA 22217		12. REPORT DATE April, 1983
		13. NUMBER OF PAGES 6
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) This document has been approved for public release and sale; its distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Submitted to Applied Physics Letters		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) picosecond x-ray picosecond photoelectron pulses		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) An x-ray source capable of producing picosecond range pulse widths at high repetition rates is demonstrated. Picosecond light pulses are converted to picosecond electron pulses which are then accelerated onto a target to produce x-rays. Using a conventional PIN diode, a time duration of less than 300 psec is observed for Al K _α x-ray emission. This x-ray source has potential applications for fast dynamic measurements of light-induced structural changes and for characterizing picosecond x-ray diagnostic equipment.		

DTIC
SELECTED
MAY 13 1983
H

DTIC FILE COPY

83 05 13 006

OFFICE OF NAVAL RESEARCH

Contract N00014-78 C-0325

TECHNICAL REPORT NO. 14

PICOSECOND X-RAY GENERATION FROM PICOSECOND
PHOTOELECTRON PULSES

BY

Steve Williamson and Gerard Mourou
Laboratory for Laser Energetics
University of Rochester
Rochester, NY 14623

AND

Charles G. Dupuy, Philippe Bado and Kent R. Wilson
Department of Chemistry, B-014
University of California at San Diego
La Jolla, CA 92093

Prepared for Publication

in

Applied Physics Letters

Reproduction in whole or in part is permitted for any purposes of the
United States Government.

This document has been approved for public release and sale; its distri-
bution is unlimited.

PICOSECOND X-RAY GENERATION FROM PICOSECOND PHOTOELECTRON PULSES

Steve Williamson and Gerard Mourou

Laboratory for Laser Energetics
University of Rochester
250 East River Road
Rochester, New York 14623

Charles G. Dupuy, Philippe Bado and Kent R. Wilson

Department of Chemistry, B-014
University of California at San Diego
La Jolla, California 92093

ABSTRACT

An x-ray source capable of producing picosecond range pulse widths at high repetition rates is demonstrated. Picosecond light pulses are converted to picosecond electron pulses which are then accelerated onto a target to produce x-rays. Using a conventional PIN diode, a time duration of less than 300 psec is observed for Al K_{α} x-ray emission. This x-ray source has potential applications for fast dynamic measurements of light-induced structural changes and for characterizing picosecond x-ray diagnostic equipment.

Submitted to Applied Physics Letters, April, 1983



Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A	

PICOSECOND X-RAY GENERATION FROM PICOSECOND PHOTOELECTRON PULSES

Steve Williamson and Gerard Mourou

Laboratory for Laser Energetics
University of Rochester
250 East River Road
Rochester, New York 14623

Charles G. Dupuy, Philippe Bado and Kent R. Wilson

Department of Chemistry, B-014
University of California at San Diego
La Jolla, California 92093

The advent of high brightness, short temporal width x-ray emission from synchrotron radiation and from laser-produced plasmas has led to the use of x-rays as a probe for kinetic studies. Dynamic measurements on the millisecond to subnanosecond time scale have been demonstrated, with current emphasis placed on resolving structural changes in biological samples.¹⁻⁷ Unfortunately, the temporal width of synchrotron radiation is limited by the characteristics of the particle accelerator,^{1,3,6} and the complexity of the equipment involved precludes its easy replication. Laser generated plasma emission suffers both from the high energy per pulse requirement which restricts it to low repetition rate lasers, and from the collisional plasma heating time which sets a lower limit to the temporal width,⁸⁻¹¹ although these restrictions might be somewhat eased by using the two pulse technique developed by Epstein et al.¹²

We report here on a simple, low cost means of producing a high-repetition rate, characteristic x-ray emitting source capable of temporal widths down to the picosecond time scale. Using an extension of earlier work done with picosecond electron diffraction,¹³ this technique involves the generation of picosecond pulses of photoelectrons which are rapidly accelerated in a high electric field and then strike an anode-target where they produce x-rays. It has been previously noted in another context that x-rays can be generated from photoelectrons in the presence of high electric fields.^{14,15} We now show that photoelectron pulses can be used to generate short x-ray bursts.

The x-ray generator shown in Fig. 1(a) consists of a flat metallic photocathode held at a large negative voltage with respect to the grounded flat anode, which also serves as the x-ray source. A metallic photocathode is used instead of the more efficient alkali halide materials so that the apparatus can function at moderate vacuum and later be opened to air. Gold is a particularly good choice in this respect as it is virtually free of oxide layers which would reduce the photoelectric efficiency. For the typical 5×10^{-5} Torr vacuum, the maximum applied voltage at the 2 cm electrode spacing is 25 kV.

The light source is the fourth harmonic of an actively-passively mode-locked Nd/YAG laser producing 15 psec pulses of approximately 10 mJ at the laser fundamental or approximately 30 μ J at 266 nm following frequency conversion (measured with a Laser Precision RJ-700 energy meter). The yield and temporal profile of the photoelectron and x-ray bursts are measured with a factory calibrated PIN diode operated at 290V DC near the breakdown voltage (Quanrad model 025 PIN-125 M). To measure the x-ray burst the diode is placed directly behind the anode-target, with a 25 μ m or 50 μ m Beryllium window to block the incident




FIG. 1. Schematic representation of the x-ray source and: (a) PIN diode detector; (b) Ga As: Cr doped picosecond detector.

electrons and scattered laser light. Using a grounded copper mesh instead of the anode target, the electron burst is measured both with the PIN diode and with a Ga As detector developed at the Laboratory for Laser Energetics,¹⁶ as shown in Fig. 1(b). Both detectors are coupled by 20 GHz semi-rigid coaxial cable to a fast oscilloscope (Tektronix model 7104 with time base 7B92A and vertical amplifier 7A29). By direct irradiation of the Ga As detector with 15 psec 266 nm laser pulses, the response of the oscilloscope is found to be approximately 250 psec.

Based on the process of electron beam conductivity, the Ga As detector can be used to measure the photoelectron pulse width and the result is shown in Fig. 2. The oscilloscope limited response of ~ 250 psec indicates that the photoelectron pulse width is on the order of the 15 psec laser pulse. It was, however, not possible to measure the x-ray emission with the Ga As detector.

The temporal profile of the x-ray burst is measured with the PIN diode and the observed signal with a 10-90% risetime of approximately 400 psec is shown in Fig. 3. The x-rays are generated from a $3 \mu\text{m}$ aluminum anode held at 20 kV with respect to the gold photocathode and are then filtered by a $25 \mu\text{m}$ Be window. To insure that the observed signal is not due to laser light or to transmitted electrons, the diode output has been checked in the absence of either laser light or high voltage. Both control conditions exhibit a random 10 mV peak-to-peak noise similar to that shown on the bottom trace of Fig. 3. Although it was not possible to fully calibrate the temporal response of the PIN diode,¹⁷ deconvoluting the ~ 250 psec oscilloscope response from the observed x-ray signal indicates that the combination of the x-ray pulse width and the PIN diode response is ~ 300 psec.




FIG. 2. Trace of the oscilloscope limited response to the photoelectron burst measured with a Ga As detector. The input laser energy at 266 nm is approximately $30 \mu\text{J}$ and the accelerating potential between the gold photocathode and the grounded copper mesh in front of the detector is 15kV. The 10 - 90 % risetime is $\sim 250 \text{ psec}$.




FIG. 3. Oscilloscope trace of the PIN diode signal from a $25 \mu\text{m}$ Be filtered burst of x-rays generated from a $3 \mu\text{m}$ aluminum anode held at 20 kV with respect to the gold photocathode. The laser input energy at 266 nm is $\sim 40 \mu\text{J}$, the measured x-ray flux is 3×10^5 into $\sim 2\pi$ steradians and the signal risetime is $\sim 400 \text{ psec}$. The bottom trace is taken with the laser light blocked and shows the random 10 mV peak-to-peak background.

The yield of photoelectrons and of subsequent x-rays is determined from the calibration curves of the PIN diode, and shows a linear dependence with input laser energy.¹⁸ Under typical operating conditions, a $30 \mu\text{J}$ pulse at 266 nm focussed to a spot size of $100 \mu\text{m}$ yields 10^7 electrons for an efficiency of approximately 10^{-6} . The yield of x-rays from electrons, measured in $\sim 2\pi$ steradian transmission through the $3 \mu\text{m}$ Al target and a $50 \mu\text{m}$ Be window, is approximately 1% for 20 kV accelerating potential. The observed factor of two drop in intensity in x-ray signal upon going from a $25 \mu\text{m}$ to a $50 \mu\text{m}$ Be window is taken as good evidence that the detected emission is indeed Al K_{α} line emission.¹⁹

Space charge broadening imposes important current density limitations on the photoelectron burst, which translate into a maximum of number of x-ray photons for a given temporal pulse width and spot size. Although durations of the observed signals are detector limited, we

believe that, due to space charge broadening,²⁰ the electron (and also the x-ray) bursts are longer than the initiating 15 psec laser pulse. In light of extensive studies in electron gun²⁰ and streak camera^{21,22} development, one can expect that an optimized design comprised of a large, curved photocathode having a high accelerating potential and a short drift region will considerably increase the maximum x-ray yield. Further work with a picosecond x-ray streak camera may more fully characterize this technique.

The feature that distinguishes the photoelectron generation of x-rays from the more common plasma or synchrotron sources is the possibility of producing very short pulses of x-rays at high repetition rates from modest input powers using comparatively simple equipment. The efficiency of the photoelectric emission can be improved by several orders of magnitude by choosing a high yield, visible light photocathode, making it possible to operate this x-ray source with low power, high repetition rate lasers (such as mode-locked Argon ion lasers). Since the x-ray bursts are well synchronized with the laser pulses, such a system would provide an attractive source of low power, high repetition rate, short x-ray probe pulses for fast dynamic measurements, using transient x-ray diffraction^{23,24} or absorption. A more immediate use for the short x-ray bursts would be to characterize picosecond x-ray diagnostic equipment.

In conclusion, an alternative source for x-ray line emission capable of operating at high repetition rates with picosecond range pulse widths is demonstrated by the use of photoelectron emission in high static electric fields. A pulse width of less than 300 psec is determined for the Al K α x-ray emission. Optimization of source geometry and of photocathode material should provide a well-synchronized, low energy probe pulse for transient diffraction or absorption studies down to the picosecond time scale to follow light-induced structural changes.

We thank the several colleagues whose advice has been essential to this work, especially Robert Frankel and James Forsyth (Laboratory for Laser Energetics), Harold Epstein (Battelle-Columbus Laboratory), and Ralph Kalibjian (Lawrence Livermore Laboratory).

This work was partially supported by the following sponsors: Exxon Research and Engineering Company, General Electric Company, Northeast Utilities, New York State Energy Research and Development Authority, Standard Oil Company (Ohio), and Empire State Electric Energy Research Corporation. Such support does not imply endorsement of the content by any of the above parties. We also thank the National Science Foundation, Chemistry and the Office of Naval Research, Chemistry for financial support and the Swiss National Foundation for fellowship support for P. Bado.

References

1. H. Winnick and S. Doniach, eds., *Synchrotron Radiation Research*, Plenum Press, New York, NY (1980).
2. H. E. Huxley, R. M. Simmons, A. R. Faruqi, M. Kress, J. Bordas, and M. H. J. Koch, "Millisecond time-resolved changes in x-ray reflections from contracting muscle during rapid mechanical transients, recorded using synchrotron radiation," *Proc. Natl. Acad. Sci. USA* 78 p. 2297 (1981).
3. J. Bordas, M. H. J. Koch, P. N. Clout, E. Dorrington, C. Boulin, and A. Gabriel, "A synchrotron radiation camera and data acquisition system for time resolved x-ray scattering studies," *J. Phys. E* 13 p. 938 (1980).
4. R. D. Frankel and J. M. Forsyth, "Applications of nanosecond x-ray diffraction techniques to bacteriorhodopsin," pp. 276 in *Methods in Enzymology*, vol. 88, ed. L. Packer, Academic Press, Inc., New York, NY (1982).
5. J. M. Forsyth and R. D. Frankel, *Flash X-Ray Diffraction from Biological Specimens Using a Laser Produced Plasma Source: A Progress Report*, Laboratory for Laser Energetics, University of Rochester, Rochester, NY (1980).

6. C. Kunz, ed., "Synchrotron radiation: techniques and applications," in *Topics in Current Physics*, vol 10, Springer-Verlag, Berlin (1979).
7. Anonymous, *Experiments with Very High-Power Lasers, Report of a Workshop, November 29-30, 1979*, Laboratory for Laser Energetics, Rochester (1980).
8. E. V. Aglitskii, A. N. Zherikhin, P. G. Kryukov, and S. V. Chekalin, "Features of x-ray spectra of a plasma produced by a subnanosecond laser pulse," *Sov. Phys. JETP* **46** p. 707 (1977).
9. E. V. Aglitsky, A. N. Zherikhin, P. G. Kriukov, and S. V. Chekalin, "X-ray spectra of plasmas created with ultrashort laser pulses," *Opt. Comm.* **20** p. 86 (1977).
10. H. D. Shay, R. A. Haas, W. L. Kruer, M. J. Boyle, D. W. Phillon, V. C. Rupert, H. N. Kornblum, F. Rainer, V. W. Slivinsky, L. N. Koppel, L. Richards, and K. G. Tirsell, "Interaction of 1.06 μ m laser radiation with variable Z targets," *Phys. Fluids* **21** p. 1634 (1978).
11. B. Yaakobi, T. Boehly, P. Bourke, Y. Conturie, R. S. Craxton, J. Delettrez, J. M. Forsyth, R. D. Frankel, L. M. Goldman, R. L. McCrory, M. C. Richardson, W. Seka, D. Shvarts, and J. M. Soures, "Characteristics of target interaction with high power UV laser radiation," *Opt. Comm.* **39** p. 175 (1981).
12. H. Epstein, "X-rays from solid state lasers," *Lasers and Applications* **1** p. 32 (1982).
13. G. Mourou and S. Williamson, "Picosecond electron diffraction," *Appl. Phys. Lett.* **41** p. 44 (1982).
14. Gy. Farkas and Z. Gy. Horvath, "Picosecond laser plasma creation in the presence of high electrostatic field on the surface of metals," *Opt. Comm.* **21** p. 408 (1977).
15. S. G. Dinev, Ch. I. Radev, K. V. Stamenov, and K. A. Stankov, "X-ray emission from a laser irradiated target in the presence of high electric field," *Opt. Comm.* **30** p. 219 (1979).
16. G. Mourou and W. Knox, "High-power switching with picosecond precision," *Appl. Phys. Lett.* **35** p. 492 (1979).
17. While calibrating the PIN diode following the x-ray measurements, the photocathode arced to the detector and significantly reduced its performance.
18. It has been shown previously under similar operating conditions that the photoelectron production from a gold photocathode varies linearly with 266 nm laser energy. S. Williamson and T. Sizer, unpublished results.
19. C. F. Hendee, S. Fine, and W. B. Brown, "Gas-flow proportional counter for soft x-ray detection," *Rev. Sci. Instr.* **27** p. 531 (1956).
20. G. A. Nagy and M. Szilágyi, *Introduction to the Theory of Space-Charge Optics*, Wiley, New York (1974).
21. R. Kalibjian, "High-intensity laser-beam effects on the spatial resolution of a streak camera tube," *J. Appl. Phys.* **46** p. 4875 (1975).
22. M. Ya. Schelev, M. C. Richardson, and A. J. Alcock, "Operation of a grid-shuttered image converter tube in the picosecond region," *Rev. Sci. Instr.* **43** p. 1819 (1972).
23. P. Bado, P. H. Berens, J. P. Bergsma, M. H. Coladonato, C. G. Dupuy, P. M. Edelsten, J. D. Kahn, K. R. Wilson, and D. R. Fredkin, "Molecular dynamics of chemical reactions in solution," in *Proceedings of the International Conference on Photochemistry and Photobiology*, ed. A. Zewail, Harwood Academic Publishers, New York (1983). In press.
24. J. P. Bergsma, M. H. Coladonato, P. M. Edelsten, J. D. Kahn, K. R. Wilson, and D. R. Fredkin, "Transient x-ray scattering from molecular dynamics," *J. Chem. Phys.*, (1983). To be submitted.

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No.</u> <u>Copies</u>		<u>No.</u> <u>Copies</u>
Office of Naval Research ATTN: Code 413 800 North Quincy Street Arlington, Virginia 22217	2	Naval Ocean Systems Center ATTN: Mr. Joe McCartney San Diego, California 92152	1
ONR Pasadena Detachment ATTN: Dr. R. J. Marcus 1030 East Green Street Pasadena, California 91106	1	Naval Weapons Center ATTN: Dr. A. B. Amster, Chemistry Division China Lake, California 93555	1
Commander, Naval Air Systems Command ATTN: Code 310C (H. Rosenwasser) Department of the Navy Washington, D. C. 20360	1	Naval Civil Engineering Laboratory ATTN: Dr. R. W. Drisko Port Hueneme, California 93401	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12	Dean William Tolles Naval Postgraduate School Monterey, California 93940	1
Dr. Fred Saalfeld Chemistry Division, Code 6100 Naval Research Laboratory Washington, D. C. 20375	1	Scientific Advisor Commandant of the Marine Corps (Code RD-1) Washington, D. C. 20380	1
U.S. Army Research Office ATTN: CRD-AA-IP P.O. Box 12211 Research Triangle Park, N.C. 27709	1	Naval Ship Research and Development Center ATTN: Dr. G. Bosmajian, Applied Chemistry Division Annapolis, Maryland 21401	1
Mr. Vincent Schaper DTNSRDC Code 2803 Annapolis, Maryland 21402		Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Naval Ocean Systems Center ATTN: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232		Mr. A. M. Anzalone Administrative Librarian PLASTEC/ARRADCOM Bldg. 3401 Dover, New Jersey 07801	1

TECHNICAL REPORT DISTRIBUTION LIST, 051B

	<u>No. Copies</u>		<u>No. Copies</u>
Professor K. Wilson Dept. of Chemistry, B014 University of California, San Diego La Jolla, California 92093	1	Dr. J. Telford University of Nevada System Desert Research Institute Lab of Atmospheric Physics Reno, Nevada 89507	1
Professor C. A. Angell Department of Chemistry Purdue University West Lafayette, Indiana 47907	1	Dr. B. Vonnegut State University of New York Earth Science Building 1400 Washington Avenue Albany, New York 12203	1
Professor P. Meijer Department of Physics Catholic University of America Washington, D. C. 20064	1	Dr. Hank Loos Laguna Research Laboratory 21421 Stans Lane Laguna Beach, California 92651	1
Dr. S. Greer Chemistry Department University of Maryland College Park, Maryland 20742	1	Dr. John Latham University of Manchester Institute of Science & Technology P.O. Box 88 Manchester, England M601QD	1
Professor P. Delahay New York University 100 Washington Square East New York, New York 10003	1		
Dr. T. Ashworth Department of Physics South Dakota School of Mines & Technology Rapid City, South Dakota 57701	1		
Dr. G. Gross New Mexico Institute of Mining & Technology Socorro, New Mexico 87801	1		
Dr. J. Kassner Space Science Research Center University of Missouri - Rolla Rolla, Missouri 65401	1		

END

FILMED

6-83

DTIC